



Trafalgar Cabinet Flammable Liquid Storage 60L

TCFLS60L 2 x 20L or 12 x 2.5L Drums (not shown)

Painted inside and out eliminating corrosion issues.

Three point self latching locking system. Easy grip handle for opening of cabinet. Lock keyed to 92268.

Fully welded 150mm deep liquid tight sump.

Self closing mechanism. Easily replaced should door be damaged

Welded shelf brackets that fully interlock with shelves. 40mm gap between brackets

Fully adjustable galvanised shelf perforated for any leakages. Easily replaced if damaged

Ventilation port with built in flame arrestor



Ventilation port with built in flame arrestor

Danger alert sign indicating specific hazardous substances stored in cabinet

Continuous piano hinge ensuring smooth closure of door

Built in ground connector



Self closing self latching door

Full instructions on usage of the cabinet attached to the inside of the door

Round corners on door

Part Number	Capacity (L)	Shelves	External Height (mm)	External Width (mm)	External Depth (mm)	Internal Height (mm)	Internal Width (mm)	Internal Depth (mm)	Weight (kg)
TCFLS60L	60	2	1065	505	460	785	420	375	62

Australian Standard

All cabinets comply with AS1940 – 2004 as follows.

1. Each cabinet is marked with the name and address of the manufacturer
2. The maximum storage capacity.
3. A Class 3 dangerous goods label with sides of at least 250mm nominal
4. A sign bearing the words "NO SMOKING, NO IGNITION SOURCES WITHIN 3M" in lettering at least 50mm high

Options

Full range of spare parts including additional shelves, closing mechanisms etc. available.

Storage

Suitable for safe storage of

1. Petrol and petroleum derivatives
2. Adhesives
3. Printing inks and solvents
4. Paints and solvents
5. Any Class 3 liquids



TRAFALGAR



CABINETS

Phone:

1800 888 714

Email:

sales@tfire.com.au

Website:

www.tfire.com.au

Trafalgar reserves the right to change specifications without notice. Please check with your supplier at the time of order.