



Trafalgar Cabinet Oxidising Agent Storage 160L

TCOAS160L

Self closing mechanism Easily replaced should door be damaged

Welded shelf brackets that fully interlock with shelves.

Fully adjustable galvanised shelves perforated for any leakages and to permit free movement of air. Easily replaced if damaged

Self closing non latching doors held shut by magnetic latches which release in the event of an internal buildup of pressure

Ventilation port with built in flame arrestor

Full instructions on usage of the cabinet attached to the inside of the door

Round corners on door.

Ventilation port with built in flame arrestor

Danger alert sign indicating specific hazardous substances stored in cabinet

Easy grip 'D' handle for easy opening of cabinet.

Continuous piano hinge ensuring smooth closure of door

Built in ground connector

Fully welded liquid tight sump capable of containing the entire contents of the cabinet

Painted inside and out eliminating corrosion issues.



Part Number	Capacity (L)	Shelves	External Height (mm)	External Width (mm)	External Depth (mm)	Internal Height (mm)	Internal Width (mm)	Internal Depth (mm)	Weight (kg)
BCOAS160L	160	2	1295	1100	460	1045	1015	375	138

Australian Standard

All cabinets comply with AS4326- 1995 as follows.

1. Each cabinet is marked with the name and address of the manufacturer
2. The maximum storage capacity.
3. A sign bearing the words "NO SMOKING, NO IGNITION SOURCES WITHIN 3M" in lettering at least 50mm high
4. Maximum quantity for storage of PG1 substances is 50kg/lt

Options

Full range of spare parts including additional shelves, closing mechanisms etc. available.

Storage

Suitable for safe storage of oxidizing agents as defined in the ADG code. Cabinets used for storage of oxidizing agents shall not be used for storage of other materials. Where more than one oxidizing agent is stored in a cabinet, the oxidizing agents shall be compatible.



TRAFALGAR



CABINETS

Phone: 1800 888 714
 Email: sales@tfire.com.au
 Website: www.tfire.com.au

Trafalgar reserves the right to change specifications without notice. Please check with your supplier at the time of order.